



NOTES:-

- 1 END COPPER STUD WILL BE ELECTRONNED 15 TO 18 MICRONS.
- 2 ELECTOLYTIC COPPER WITH HIGH ELECTRICAL CONDUCTIVITY.
- 3 COLOUR BRICK RED.
- 4 ALL DIMENSION ARE IN MM.

ELECTRICAL SPECIFICATION

- 1 RATED VOLTAGE.....12kv
- 2 ONE MINUT DRY WITHSTAND VOLTAGE....42kv
- 3 RATED CURRENT.....400amp
- 4 IMPLUSE WITHSTAND VOLTAGE.....75kvp
- 5 CREEPAGE DISTANCE.....31mm/kv



01	12 kv/400amp	DISCRPTION		EPOXY RESINE CAST BUSHING		DRN.	SIGN	DATE
TYPE		ITEM CODE: FF0106		CHD.	AP	TANVI	AP	05.06.2010
* DO NOT SCALE THE DRAWING		MANUFACTURER		APPD.				
		Fibre & Fibre Glass Products 250/7, MAGAZINE HOUSE G.I.D.C. MAKARPURA, VADODARA- 390010		DRAWING NO.:		Sheet Edition		REV
				FFGP-050/09-10		1/1		0
								0

A B C D E F

1 2 3 4