

**MECHANICAL SPECIFICATION**

IS:9431-1979

- 1 TENSILE FALLING LOAD.....1000Kg
- 2 COMPRESSION FALLING LOAD.....10000Kg
- 3 CANTILEVER FALLINGS LOAD.....500Kg


**ELECTRICAL SPECIFICATION**

IS:9431-1979

- 1 RATED VOLTAGE.....11kv
  - 2 DRY POWER FREQUENCY WITHSTAND VOLTAGE TEST(ONE MINUT).....35kv
  - 3 MINIMUM CREEPAGE DISTANCE.....175mm
  - 4 DRY LIGHTING IMPULS WITHSTAND VOLATAGE TEST.....95kv Peak
- OTHERS**
- 1 COLOUR BRICK RED.
  - 2 ALL DIMENSION ARE IN MM.

M8 x 20mm  
DEEP IN 2NO

02	BRASS INSERTS	DISCRPTION
01	M.S INSERT WITH WHITE ZINK PLATING	



11kv EPOXY RESINE CAST INSULATOR		
ITEM CODE: FF0088		
DRN.	SIGN	DATE
CHD.	TANVI	12/05/09
APPD.	AP	-



**MANUFACTURER**  
Fibre & Fibre Glass Products  
250/7, MAGAZINE HOUSE  
G.I.D.C. MAKARPURA,  
VADODRA- 390010

**DRAWING NO.:**  
FFGP-035/09-10

Sheet Edition  
1/1 0 REV 0